

DATASHEET

UHF Micro Tag

Tag Code: U3411510

Micro tag is the UHF mount on metal tag, which for its size provides unparallel performance. It offers new possibilities for companies to improve their Asset management, especially computers and other devices that contain variable information.



Electrical Specification


Air Interface Protocol	ISO/IEC 18000-6C, EPC Global C1G2
Operational Frequency	865 – 868 MHz or 902 – 928 MHz
Chip**	Alien Higgs-3
Memory Configuration	EPC-96 bits, extendible to 480bits
	TID – 96 bits unalterable unique
	User memory – 512 bits
	Access password – 32 bits
	Kill password – 32 bits
Read Range*	On metal – Up to 7 m Off metal – Up to 2 m

Physical / Mechanical Specification

Dimensions	52 x 16 x 8.5 ± 0.2 mm
Colour**	Grey
Weight	5 g
Encasement	PC / ABS High Impact
Quality Assurance	100% reader tested

Environmental Resistance

Operating temperature	-40°C to +85°C
Storage temperature	-40°C to +85°C
Ingress protection rating	IP67
Attachment***	Riveting/Screw/Magnetic/Adhesive
Applicable surface	Metal



Chemical Resistance


Resistant to continuous exposure to salt water for 2 hours


Resistant to continuous exposure to motor oil for 2 hours


Additionally, abrasion resistant against HCL and IPA

Additional Services

Pre-encoding	On request
Customization***	Logo / text printing on request







Order Information

Part No.	Description
U3411510-EU	Alien higgs-3 chip tuned at ETSI frequency
U3411510-US	Alien higgs-3 chip tuned at US frequency
U3411512-EU	Alien higgs-4 chip tuned at ETSI frequency
U3411512-US	Alien higgs-4 chip tuned at US frequency

